



EcoStrip 9380

Welcome to the Future of Entry Level Cut & Strip

- Roller or belt feeding unit
- Improved price to performance ratio
- Simple programming with Schleuniger's standardized S.ON user interface
- The latest technology, cleverly combined with Schleuniger's industry renowned precision
- Compatible with MES CAO via SMG Server and CAYMAN software

CUT & STRIP

EcoStrip 9380




Simply Capable

Transforming your expectations: Flexible cut and strip machine equipped with roller or belt feeding unit capable of short mode processing.

Cut your cost, strip your efforts: The machine is economically priced, yet in terms of performance, it exceeds previous models by 20 percent.

Explore simplicity: Simple programming via 5.7" color touchscreen with Schleuniger's standardized S.ON user interface.

Precision has a name: All driven axes are powered by our proven *Bricks* electronic platform for ultimate precision.



The EcoStrip 9380 capabilities are significantly expanded due to quick change feeding unit for rollers, belts and short mode processing.

Compatible with a wide range of accessories (prefeeding, marking, stacking, coiling and tying) for future expansion.

Minimize training and setup time with S.ON software. Cayman and S.WOP compatible for integration into various networks.

Technical Specifications	
Raw Material Diameter	0.3 – 8.0 mm (0.012 - 0.31")
Conductor Cross-Section	0.05 – 8 mm ² (10 mm ² EN60228 class 5&6) 36 – 8 AWG (depending on cable)
Blade Set	Up to 1 x 12 mm (1 x 0.47") wide
Feeding Unit	Rollers or Belts
Single conductor (1 step)	Yes
Multi-layer Single conductor	Yes
Workpiece Length	1,000,000 mm (39,370")
Pull-off length	Left Side: 46 mm (1.18") Right Side: 152 mm (5.98")
Short Mode	Up to 46 mm (18 mm measured on remaining insulation length)
Interfaces	Standard: Ethernet for PC, USB Optional: SMI (I/O's), Prefeeder, Wire marker (HS), Inkjet printing, Stacker / Coiler
Power Supply	100-240 VAC
Dimensions (L x W x H)	435 x 397 x 360 mm (17.1 x 15.6 x 14.2")
Weight	25 kg (55.1 lbs.)
CE – Conformity	The EcoStrip 9380 complies fully with all CE and EMC equipment guidelines relative to mechanical and electrical safety and electromagnetic compatibility.
Important note	Schleuniger recommends that wire samples be submitted in cases where there is doubt as to the processing capabilities of a particular machine.